φ



9 Seats Ford Transit Ambulance 6 Seater Medi Cal Ambulance Front Rear Drive 4x2

Basic Information

• Place of Origin: . Brand Name:

Model Number: Ford long-axis medical vehicle diesel 9-seat

front rear drive 4×2 long-row warning lights

on the roof.

• Minimum Order Quantity: 1vehicle

• Price: 50000-80000 dollar

 Packaging Details: entire car Delivery Time: 5-8week days T/T • Payment Terms: 1000 vehicle Supply Ability:



Product Specification

• Air Conditioning: Yes Communication System: Yes • Emergency Lights: Yes

Fuel Type: Gasoline/Diesel

· GPS: Yes Medical Equipment: Yes Medical Supplies: Yes Power Supply: Yes

Product Name: Medical Emergency Ambulance

Safety Features: Yes Seating Capacity: 9 Seats Size: Medium Vehicle Type: Ambulance

Highlight: 9 Seats Ford Transit Ambulance. 6 Seater Medi Cal Ambulance,



More Images











Product Description

Ford long-axis medical vehicle diesel 9-seat front rear drive 4×2 long-row warning lights on the roof.

Basic configuration: the exterior surface color of the car body is white, side sliding doors, new front face (bright black paint), LED daytime running lights, LED interior lights, central locking, front electric windows, reversing radar, and bumper with the

same color as the car body.

Appearance identification: made according to customer requirements.

Alarm: 1 100W controller with multi-gear adjustment, with microphone calling function, which conforms to the tone of China ambulance national standard, can be used for 24 hours and controlled by the cab.

4 warning lights: Long rows of LED warning lights and 3 embedded flash lights are installed on the forehead of the roof, which can effectively warn pedestrians and vehicles

5 Flash blocks: 3 square LED flash lights on both sides of the top of the car body, 2 square LED flash lights on the rear of the car body, and 1 embedded LED corner flash light on the left and right corners of the rear, which can effectively warn passersby and vehicles.

6 basic vehicle parameters:

7 Fuel: diesel oil

8 Basic overall dimensions (length× width× height mm) mm): $5820 \times 1974 \times 2640$. 9 wheelbase (mm): 3750

10 Top speed (km/h): 145 11 tires: 215/75 r 16 lt

12 Suspension type: front torsion bar spring independent suspension, rear longitudinal leaf spring.

13 curb weight (kg): 2780

14 Total mass (kg): 3700 15 rated passenger (person): 6-9 16 Braking mode: front and rear disc braking.

17 Brake Assist: Four-wheel Anti-lock Brake System (ABS EBD)

18 Safety and theft prevention: driver's airbag+pretensioned seat belt, passenger seat belt adjustable, three-point seat belt for the whole vehicle, ESP+HHC, cruise control, automatic headlights, automatic wiper, battery management system, PATS electronic anti-theft system, high-position brake light and tire pressure monitoring system.

Comfort and convenience: 3.5-inch LCD instrument +10.1-inch central control display screen, multi-function steering wheel, independent adjustable backrest of double co-driver, high-power air conditioning, six-way adjustment of driver's seat. 20 dynamic performance:

Engine: turbocharged diesel engine Transmission: 6-speed manual transmission.

23 displacement (ml): 2198 24 rated power (kw): 103

25 Fuel and oil consumption: 26 fuel type: diesel oil

27 Fuel tank volume (L): 80 Fuel consumption per 28km (L/100km): 9.7

29 Emission standard: GB17691-2018 Country VI

30 axis number 2

31 approach angle/Departure Angle: 22/24

32 Front suspension/rear suspension (mm) 973/1097

33 Axial load: 1690/2010

34 Front track: 1740

35 Rear track: 1704 36 Number of tires: 4

37 Steering form steering wheel

38 medical warehouse requirements: Basic dimensions of medical cabin (length× width× height mm): 3230× 1730× 1800.

40 cockpit medical compartment partition board: it runs through the car body horizontally, and the two compartments are completely separated, with front and rear intercom.

Observation window on partition: metal window frame, push-pull plexiglass window.

Floor: the bottom floor is shock-absorbing floor, and the upper floor is anti-slip, anti-static and medical washable floor. Characteristics of interior materials in Medical Warehouse: It is mildew-proof, bacteria-proof, antistatic, moisture-proof, flame-retardant, easy to clean, easy to disinfect, high in strength, anti-aging, odorless, non-toxic and safe.

44 Fire protection requirements: The fire protection performance of the interior structure and decorative materials should meet the requirements of GB8410 1994 "Combustion Characteristics of Automobile interior materials".

45 Cabin lighting: 6 LED fluorescent tubes (with adjustable brightness) and 2 spotlights to ensure the illumination in the cabin. 46 Rear Lighting One LED lighting lamp is installed at the rear of the medical cabin.
47 Sterilization and disinfection system: 12V ultraviolet disinfection lamp, which can be turned on automatically with delay. The

installation and use meet the Technical Specification for Disinfection, and the upper part of sliding window of partition wall is

48 Slide-rail infusion hangers: 2 infusion bottle holders, each with a load of 2.5kg, to meet the requirement of instant infusion for patients in walking/parking state.

49 Anti-bacterial Safety Handrails A 2m-long safety handrail is installed in the medical cabin, a safety handrail is installed on the right inner upper wall, and a safety handrail is installed at the lower long seat end. (Provide pictures of real cars as

50 The rear pedal protection device is made of stainless steel.

51 Protective soft bag Install protective soft bag in the right middle part of the medical cabin

52 Right side 3-person in-line seat cabinet plus independent escort seat: single-person nurse seat with adjustable back on the right side of medical cabin with seat belt, three-person long row seat: with comfortable back, soft cushion and seat belt.

53. Install a one-person cabinet behind the partition wall of the independent cabinet.

54. Install a set of lockers behind the partition wall of lockers (articles and first aid boxes can be placed).

55. air outlet form: the front top above the partition wall of the medical cabin is ventilated backwards. Refrigeration requirements: compressor refrigeration

57. Ventilation and ventilator: the overhead ventilator enters and exits the system, and the voltage is controlled by 12V.

58. oxygen supply system:

59.oxygen cylinder: Double 10L oxygen cylinders (including decompression device) and fixed. 60.oxygen interface: 2

61. Humidification bottles:

62. Oxygen pipeline: concealed and auxiliary, and the pipeline meets medical standards. 63. oxygen valve: 2 sets.

Oxygen cabinet: light environmental protection material.

65. automatic boarding stretcher. 66, shovel stretcher



















No. 15, Wuxing 4th Road, Wuhou District, Chengdu City